AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application;

1. (Currently Amended) A video signal processing circuit is characterized by comprising:

analog/digital converting means, ~~which is capable of~~ <u>for</u> inputting a composite video signal of a ~~different~~ <u>first</u> system with ~~different frequency of~~ a <u>first</u> color burst signal <u>frequency, said first system and said first color burst signal frequency being different than a second system having a second color burst signal frequency, and</u> for converting an inputted <u>analog</u> composite video signal ~~as an analog signal~~ to a <u>digital</u> composite video signal ~~as a digital signal~~ by sampling with a sampling frequency in accordance with a system clock;

video signal processing means for executing a YC separation process for separating a luminance signal and a chroma signal from said <u>digital</u> composite video signal ~~as said digital signal,~~ and <u>for executing</u> a chroma demodulation process for demodulating said chroma signal obtained by said YC separation process, at a predetermined timing based on said system clock; and

system clock generating means for generating said system clock synchronized with ~~said~~ <u>a</u> color burst signal extracted from said <u>digital</u> composite video signal, and configured to change and set a coefficient n in accordance with a system of

3

said composite video signal inputted to said video signal processing means so [[as]] that a frequency m falls in a predetermined range between said ~~different~~ first and second systems, in a case where a frequency of said color burst signal is defined as fsc, a coefficient is defined as n, and a frequency m of said system clock is represented by fsc x n = m.

2. (Currently Amended) The video signal processing circuit according to claim 1 ~~is characterized by~~ further comprising:

~~low pass~~ low-pass filter means~~, in which~~ having a ~~cut off~~ cut-off frequency [[is]] set in accordance with said sampling frequency [[at]] of said analog/digital converting means, for passing said inputted analog composite video signal ~~as an analog signal~~ through a band under said ~~cut off~~ cut-off frequency to ~~output to~~ said analog/digital converting means.

3. (Currently Amended) The video signal processing circuit according to claim 1 ~~is characterized by~~ further comprising:

~~low pass~~ low-pass filter means, to which said digital composite video signal ~~as a digital signal~~ outputted from said analog/digital converting means [[are]] is inputted, for passing said inputted composite video signal through a band under a predetermined ~~cut of~~ cut-off frequency to ~~output at least to~~ said video signal processing means.

4

4. (Currently Amended) The video signal processing circuit according to claim 1 ~~is characterized by~~ <u>further</u> comprising:

a determination circuit for determining said <u>first</u> system <u>or said second system</u> of said <u>inputted</u> composite video signal ~~to be inputted,~~ based on a state of synchronization with said color burst extracted from said composite video signal [[if]] <u>when</u> said system clock frequency is switched; and

signal switching means for outputting a composite video signal after conversion to said digital signal by said analog/digital converting means, instead of said luminance signal obtained by said video signal processing means, during said determination operation [[is]] executed by said determination circuit.

5. (Currently Amended) The video signal processing circuit according to claim 1 ~~is characterized in that:~~<u>, wherein</u>

said ~~imaging~~ <u>video</u> signal processing means is configured to execute an operation based on a system clock frequency represented by fsc x a, where a frequency of a color burst signal is defined as fsc and a coefficient is defined as a (a relation between said coefficient a and said coefficient n is a < n); and <u>further comprising</u>

decimating sample means [[is]] provided at a previous stage of said ~~imaging~~ <u>video</u> signal processing means, for

5

executing a sampling process on said inputted composite video signal as a digital signal based on a decimating rate determined by a relation between said coefficient a and said coefficient n.

6. (Currently Amended) The video signal processing circuit according to claim 1 ~~is characterized in that:~~, wherein

said system clock generating means ~~is capable of generating~~ generates a system clock of a frequency b different from a frequency m a corresponding to a component signal;

and further comprising:

analog/digital inverting means corresponding to said component signal, which is provided every predetermined number of signals forming said component signal, for converting an inputted analog composite video signal ~~as an analog signal~~ to [[an]] a digital composite video signal ~~as a digital signal~~ by sampling with a sampling frequency in accordance with a system clock of said frequency b; and

~~low pass~~ low-pass filter means corresponding to a component signal, which is provided at a previous stage of said analog/digital inverting means corresponding to a component signal, for passing an inputted signal through a band under a ~~cut off~~ cut-off frequency set based on a sampling frequency of said analog/digital inverting means corresponding to a component signal;

wherein said coefficient n is set so that a system clock having a frequency m generated by said system clock generating means has a frequency difference ~~that~~ falls in a predetermined range with respect to said frequency b.

7. (Currently Amended) A video signal processing method ~~is characterized by~~ comprising:

an analog/digital converting process, ~~which is capable of~~ for inputting a composite video signal of a ~~different~~ first system with ~~different frequency of~~ a first color burst signal frequency, said first system and said first color burst signal frequency being different than a second system with a second color burst signal frequency, and for converting said inputted composite video signal as an analog signal to a composite video signal as a digital signal by sampling with a sampling frequency in accordance with a system clock;

a video signal processing process for executing a YC separation operation for separating a luminance signal and a chroma signal from said composite video signal as said digital signal, and a chroma demodulation operation for demodulating said chroma signal obtained by said YC separation process, at a predetermined timing based on said system clock; and

a system clock generating process for generating said system clock synchronized with said color burst signal extracted from said composite video signal, and configured to

7

change and set a coefficient n in accordance with a system of said composite video signal inputted to said video signal processing ~~means~~ <u>process</u> so [[as]] that a frequency m falls in a predetermined range between said ~~different~~ <u>first and second</u> systems, in a case where a frequency of said color burst signal is defined as fsc, a coefficient is defined as n, and a frequency m of said system clock is represented by fsc x n = m.